

## JAZEE PRO specifications

Feature	Model					
	2148KAJ-SR360	2148KAT-SR360	2748KOJ-SR360	2748KOT-SR360	2152KAJ-SR360	2152KAT-SR360
Engine	Kawasaki V-Twin		Kohler Courage Pro		Kawasaki V-Twin	
Horsepower	21 hp		27 hp		21 hp	
Cylinders	Twin					
Oil Capacity	2 qt w/ filter					
Transmission	Twin HydroGear ZT-2800 w/ charge pump					
Steering Control	Joystick	Dual Lever	Joystick	Dual Lever	Joystick	Dual Lever
Fuel Capacity	4.5 gal					
Tires, Rear	20 x 10.00 - 10			20 x 12.00 - 10		
Tires, Front	13.50 x 6.00 - 5					
Turning Radius	Zero-Turn					
Ground Speed Forward	8 mph					
Reverse	5 mph					
Length	77"					
Height: top of seat back	43"					
Width, Tractor (outside rear tires)	46"					
Deck, Width w/chute	58"			62"		
Cutting Width	48"			52"		
Blade Length (each of 3)	17"			18 3/8"		
Spindle Assembly	Cast iron housing and 1.125" shaft (Spindle Pulleys also machined cast iron)					
Deck Construction	Full complement front/rear baffles, reinforced bullnose front; fabricated, multi-layered laminated deck shell, 3 blades, anti-scalp rollers, stand-up deck					
Cutting Height	1.5" to 4.5"					
Blade Clutch	Electric					
Blade Tip Speed	19,000 fpm					
Weight	760 lbs		775 lbs			
Electric Start	Standard					
Hour Meter	Standard					
Cup Holder	Standard					
Arm Rests	Standard					
Head Light Kit	Option					
Mulch Kit	Option					
Pivoting Front End	Standard					

Due to continuous product improvement, all specifications are subject to change without notice.

## JAZEE PRO specifications

Feature	Model				
	2752KOJ-SR360	2752KOJL-SR360	2752KOT-SR360	2760KOJ-SR360	2760KOT-SR360
Engine	Kohler Courage Pro				
Horsepower	27 hp				
Cylinders	Twin				
Oil Capacity	2 qt w/ filter				
Transmission	Twin HydroGear ZT-2800 w/ charge pump				
Steering Control	Joystick	Joystick - <b>Left Hand</b>	Dual Lever	Joystick	Dual Lever
Fuel Capacity	4.5 gal				
Tires, Rear	20 x 12.00 - 10				
Tires, Front	13.50 x 6.00 - 5				
Turning Radius	Zero-Turn				
Ground Speed Forward	8 mph				
Reverse	5 mph				
Length	77"				
Height: top of seat back	43"				
Width, Tractor (outside rear tires)	49"				
Deck, Width w/chute	62"			70"	
Cutting Width	52"			60"	
Blade Length (each of 3)	18 <sup>3</sup> / <sub>8</sub> "			21"	
Spindle Assembly	Cast iron housing and 1.125" shaft (Spindle Pulleys also machined cast iron)				
Deck Construction	Full complement front/rear baffles, reinforced bullnose front; fabricated, multi-layered laminated deck shell, 3 blades, anti-scalp rollers, stand-up deck				
Cutting Height	1.5" to 4.5"				
Blade Clutch	Electric				
Blade Tip Speed	19,000 fpm				
Weight	775 lbs			800 lbs	
Electric Start	Standard				
Hour Meter	Standard				
Cup Holder	Standard				
Arm Rests	Standard				
Head Light Kit	Option				
Mulch Kit	Option				
Pivoting Front End	Standard				
Due to continuous product improvement, all specifications are subject to change without notice.					